

What is claimed is:

1. A nonwoven safety garment, comprising:
a piece of cut spunbond/melt blown/melt blown/spunbond material having
at least one cut edge;
a plurality of hems stitched into the material and defining a garment;
wherein the hems are characterized by between 10 and 12 stitches per
inch;
wherein the at least one cut edge is double-folded under; and
wherein the at least one double-folded edge is hemmed into place.
2. The garment of claim 1 wherein the garment further includes a plurality
of snap-fasteners and wherein the garment is shaped to form a smock.
3. The garment of claim 1 wherein the garment further includes a plurality
of snap-fasteners and wherein the garment is shaped to form a jumpsuit.
4. The garment of claim 1 wherein the garment further includes an elastic
band disposed under a hem and wherein the garment is shaped to form a shoe covering.

5. A disposable clean room safety garment, comprising:
 - at least one sheet of nonwoven fabric defining at least one cut edge;
 - a plurality of stitches formed in the at least one sheet of nonwoven fabric to define a garment; and
 - hems formed at the at least one cut edge;
 - said nonwoven fabric being formed from spunbond/meltblown material;
 - said plurality of stitches characterized by respective stitch densities of between ten and twelve stitches per inch; and
 - said hems characterized by respective stitch densities of between ten and twelve stitches per inch.
6. The garment of claim 5 wherein the garment further includes a plurality of snap-fasteners and wherein the garment is shaped to form a smock.
7. The garment of claim 5 wherein the garment further includes a plurality of snap-fasteners and wherein the garment is shaped to form a jumpsuit.
8. The garment of claim 5 wherein the garment further includes an elastic band disposed under a hem and wherein the garment is shaped to form a shoe covering.
9. The garment of claim 5 wherein the at least one sheet of nonwoven fabric is a plurality of sheets of nonwoven fabric.
10. The garment of claim 5 wherein the hems are folded twice to encapsulate the at least one cut edge.

11. A method of making a safety garment, comprising the steps of:

a) cutting at least one sheet of nonwoven material into a safety garment

pattern;

b) stitching the at least one to defining a garment;

c) hemming the garment;

wherein all cut edges are twice folded and hemmed under to prevent exposure of any cut edges;

wherein all stitching is characterized by a stitch density in the range of 10 to 12 stitches per inch.